LITZ CRYO 45%

:Litz
Created by
INSTALLERS, FOR INSTALLERS

Description of the film

Automotive dual-layer film with a thickness of 1.8 mil, designed for vehicle window tinting and protection against excessive heat gain. A ceramic coating with 150 nm particles provides both effective darkening and high heat rejection. This innovative ceramic technology ensures excellent solar control while maintaining clear visibility and long-lasting performance.

INSPECTION ITEMS	TEST METHOD	TEST VALUE
Cosmetic Appearance	Visual Inspection	Complies
Width	GB/T 13542.2	1560mm
Thickness	GB/T 13542.2	1,8 mil
Visible Light Transmittance (VLT)	GB/T 2680	44,9%
Ultraviolet Rejection (UVR)	GB/T 2680	99,9%
Infrared Rejection (IRR)	GB/T 2680	78,0%
Color Consistency	Visual Inspection	Complies
Haze Ratio	GB/T 5137.1	1%
Adhesive Properties	GB/T 31849	660,97 gf
Thermal shrinkage rate (MD)	GB/T 13542.2	1,22%
Fade Resistance Warranty		10 years

All statements, technical inforamtion, and recommendations provided in this document are based on tests that :Litz believes to be reliable.
However, :Litz does not guarantee the accuracy or completem=ness of this information.