
LITZ ULTRA SOFT

Transparent, glossy polyurethane film for protecting paint and other surfaces from chips and scratches.
Suitable for both exterior and interior use.

:Litz
Created by
INSTALLERS, FOR INSTALLERS

Film structure

	Total film thickness	190 Micron
1	Transport liner	50.8 Micron
2	Top polyurethane layer	9.7 Micron
3	Base polyurethane layer	152.2 Micron
4	Adhesive layer	28.1 Micron
5	Liner	88.9 Micron



INSPECTION ITEMS	TEST METHOD	STANDARD	VALUE
Color	Visual inspection	Transparent	Transparent
Film surface type	Visual inspection	Glossy	Glossy
Self-healing	Copper brush 10 times, 1 min in hot water (50–70°C)	100%	100%
Film peel resistance (after 20 minutes)	GB/T 2792	>2,32 H/см	5,14 H/см
Film peel resistance (after 24 hours)	GB/T 2792	>2,32 H/см	6,86 H/см
Stretchability at break of the top layer	GB/T 1040.1	>80%	150%
Stretchability at break of the film	GB/T 1040.1	>200%	361,60%
Tear resistance (whole film)	GB/T 1040.1	>15 Mpa	28,9 Mpa
Force for double elongation	GB/T 1040.1	>6 Mpa	7 Mpa
Operating temperature range			-30C ~ +80C
Warranty (delamination, yellowing, hazing)			10 years

All statements, technical information, and recommendations contained in this document are based on tests that :Litz considers reliable. However, :Litz does not guarantee the accuracy or completeness of this information.